

PROPERTIES

Snow-white, superlight, elastic repair and finishing plaster

1. Ready to use indoors and outdoors.
2. Easy to use paste.
3. Grain-free structure:
 - easy to spread smoothly
 - super fine result
 - cuts down on sanding
4. Excellent bond on all porous constructions materials.
5. Water-resistant and can be quickly painted over.
6. Handles shrinkage and expansion without tearing.
7. Keeps for a long time, even after having been open frequently.



TECHNICAL INFORMATION

Viscosity: paste

Density: (23°C): 0,420 +/- 0,010gr/cm³

Base: water

hardening: shrinkage and tear-free

Can be painted over:

- waterborne coatings: after +/- 1u
- synthetic paint: +/- 24h

Storage life: 24 months, dry, cool and frost-free

Safety measures: please consult safety data sheet

APPLICATIONS

Snow-white, superlight, elastic repair and finishing plaster for filling holes, tears and joints in walls and ceilings, plaster and stucco, plasterboard, gypsum board and blocks, wood, soft board and hard board, stone, limestone, porous concrete and all porous construction materials.

For professional repairs of damages on painted or plastered surfaces.

Can be painted over quickly.

TEC7 Filler is the perfect preparation and ensure a smooth finish before painting, hanging or decorating walls and ceilings, woodwork, plasterboard and stucco.

Not suitable for use on surfaces such as metal or plastic.



PACKAGING

Content: 250 ml - 750 ml - 5 l - 300 ml

Abbreviation: Fil7

	Article number
Jar TEC7 Filler 250 ml	601025000
Jar TEC7 Filler 750 ml	601075000
Bucket TEC7 Filler 5 l	601005000
Cartridge TEC7 Filler 300 ml	601106000

USE

TEC7 Apply filler on a dry, dust-free and grease-free surface, free of loose paint chips, plaster, etc.

To strengthen weak and/or loose surfaces, treating beforehand with EPOFIX7 (fixer) is recommended.

To obtain quicker hardening with repairs deeper than 3 cm, build TEC7 Filler up in layers.

