

PROPERTIES

- this rubbery repair paste is a unique roof repair product formulated with rubber for a longer service life, and with glass fibres for greater strength.
- remains soft and flexible for up to 20 years after application.
- can be applied at temperatures from -12°C to +50°C, and this on a dry or wet substrate, without dissolving or rinsing away.



TECHNICAL INFORMATION

Flash point: 38°C (minimum)

Modified asphalt content: 50 %

Solid components: 70 %

Tensile strength (dry film): 200 PSI

Elongation at break (dry film): 150 %

Temperature resistance: from -40°C to +82°C

UV-resistance: very good

Climatological resistance: good

Water resistance with adequate run off: very good

Application temperature: from -12°C to +50°C

Do not apply if there is snow or ice.

APPLICATIONS

- repair of flat and sloping roofs with bituminous roof covering
- sealing of chimneys, roof gutters, eaves, compression strips, roof feed-throughs, ...
- waterproofing of foundations and walls, flat and sloping roofs, domes, terraces and balconies
- as cold adhesive to bond bituminous materials (roofing, shingles, rooftiles)
- fixing of counter flashing
- immediate sealing of leaking roofs (wet substrates)



Industrielaan 5B - 2250 Olen - Belgium
 t +32 14 85 97 37 - f +32 14 85 97 38
 info@tec7.be - www.tec7.com
 ISO Certified Company ISO 9001:2000 - ISO 14001:2004 - OHSAS 18001:2007

PACKAGING

ROOF7	Article Number
Cartridge 310 ml	602116000
Pot 1 kg	602201000
Pot 5 kg	602204000
Pot 10 kg	602210000

