SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

GT7 AEROSOL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **Registration number REACH** Product type REACH

: GT7 AEROSOL : Not applicable (mixture) : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Lubricating oil

Detergent according to Regulation (EC) No 648/2004

1.2.2 Uses advised against

No uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

TEC7* Industrielaan 5B B-2250 Olen +32 14 85 97 37 **₼** +32 14 85 97 38 info@tec7.be *TEC7 is a registered trademark of Novatech International Industrielaan 5B

Manufacturer of the product

Novatech International N.V. Industrielaan 5B B-2250 Olen +32 14 85 97 37 **i □** +32 14 85 97 38 info@tec7.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as danger	Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008					
Class Category Hazard statements						
Aerosol	category 1	H222: Extremely flammable aerosol.				
Aerosol	Aerosol category 1 H229: Pressurised container: May burst if heated.					

2.2. Label elements

Signal word	Danger		
H-statements			
H222	Extremely flammable aerosol.		
H229	Pressurised container: May burst if heated.		
P-statements			
P102	Keep out of reach of children.		
P210	Keep away from heat, hot surfaces, sparks, op	en flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition	on source.	
P251	Do not pierce or burn, even after use.		
P410 + P412	Protect from sunlight. Do not expose to temp	eratures exceeding 50 °C/ 122°F.	
Created by: Brandweerinformatiece	ntrum voor gevaarlijke stoffen vzw (BIG)	Publication date: 2008-03-20)-en
Technische Schoolstraat 43 A, B-244	l0 Geel	Date of revision: 2016-06-14	134-16433-500-en
http://www.big.be © BIG vzw			6433
Reason for revision: 3.2; 13; 15.1			.34-1
Revision number: 0602		Product number: 44875	1/13

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
white mineral oil (petroleum) 01-2119487078-27	8042-47-5 232-455-8	15% <c<30%< td=""><td>Asp. Tox. 1; H304</td><td>(1)(2)(10)</td><td>Constituent</td></c<30%<>	Asp. Tox. 1; H304	(1)(2)(10)	Constituent
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119457273-39		15% <c<30%< td=""><td>Asp. Tox. 1; H304</td><td>(1)(10)</td><td>Constituent</td></c<30%<>	Asp. Tox. 1; H304	(1)(10)	Constituent
propane 01-2119486944-21	74-98-6 200-827-9		Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
butane 01-2119474691-32	106-97-8 203-448-7		Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Rinse with water. Take victim to a doctor if irritation persists.

After eye contact:

Rinse with water. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms
 After inhalation:
 EXPOSURE TO HIGH CONCENTRATIONS: Headache. Vomiting. Abdominal pain. Disturbances of consciousness.
 After skin contact:
 No effects known.

After eye contact:

Redness of the eye tissue.

After ingestion: No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

- Water spray. Polyvalent foam. BC powder. Carbon dioxide.
- 5.1.2 Unsuitable extinguishing media:
- No unsuitable extinguishing media known.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

Reason for revision: 3.2; 13; 15.1

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Protect against frost. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Belgium

Huiles minérales (brouillards)	Time-weighted average exposure limit 8 h	5 mg/m³
	Short time value	10 mg/m³
Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1- C4)	Time-weighted average exposure limit 8 h	1000 ppm

The Netherlands

	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	592 ppm
	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	1430 mg/m ³
,	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	5 mg/m³

Reason for revision: 3.2; 13; 15.1

France		
France n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m
Germany		
Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m
Weißes Mineralöl (Erdöl)	Time-weighted average exposure limit 8 h (TRGS 900)	5 mg/m ³
ик		
Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m
USA (TLV-ACGIH)		
Butane, all isomers	Short time value (TLV - Adopted Value)	1000 ppm
Mineral oil, pure, highly and severely re (I): Inhalable fraction	efined Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m³ (I)
If applicable and available it will be liste 8.1.5 Control banding	ed below.	
 8.1.5 Control banding If applicable and available it will be listed. Exposure controls The information in this section is a general scenarios that correspond to your identifie 8.2.1 Appropriate engineering controls Use spark-/explosionproof appliances a concentration in the air regularly. 8.2.2 Individual protection measures, such Observe normal hygiene standards. Do	ed below. I description. If applicable and available, exposure scenarios are attached in annex. Always use the ed use. and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks h as personal protective equipment	
 8.1.5 Control banding If applicable and available it will be listed. Exposure controls The information in this section is a general scenarios that correspond to your identifie 8.2.1 Appropriate engineering controls Use spark-/explosionproof appliances a concentration in the air regularly. 8.2.2 Individual protection measures, such Observe normal hygiene standards. Do a) Respiratory protection: Wear gas mask with filter type A if controls b) Hand protection:	ed below. I description. If applicable and available, exposure scenarios are attached in annex. Always use the ed use. and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks h as personal protective equipment o not eat, drink or smoke during work.	
 8.1.5 Control banding If applicable and available it will be listed. Exposure controls The information in this section is a general scenarios that correspond to your identifie 8.2.1 Appropriate engineering controls Use spark-/explosionproof appliances a concentration in the air regularly. 8.2.2 Individual protection measures, such Observe normal hygiene standards. Do a) Respiratory protection: Wear gas mask with filter type A if concentration	ed below. I description. If applicable and available, exposure scenarios are attached in annex. Always use the ed use. and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks h as personal protective equipment o not eat, drink or smoke during work. c. in air > exposure limit.	
 8.1.5 Control banding If applicable and available it will be listed. Exposure controls The information in this section is a general scenarios that correspond to your identifie 8.2.1 Appropriate engineering controls Use spark-/explosionproof appliances a concentration in the air regularly. 8.2.2 Individual protection measures, such Observe normal hygiene standards. Do a) Respiratory protection: Wear gas mask with filter type A if conteb b) Hand protection: Gloves. Materials nitrile rubber	ed below. I description. If applicable and available, exposure scenarios are attached in annex. Always use the ed use. and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks h as personal protective equipment o not eat, drink or smoke during work.	
 8.1.5 Control banding If applicable and available it will be listed. If applicable and available it will be listed. Exposure controls The information in this section is a general scenarios that correspond to your identified. 8.2.1 Appropriate engineering controls Use spark-/explosionproof appliances a concentration in the air regularly. 8.2.2 Individual protection measures, such Observe normal hygiene standards. Do a) Respiratory protection: Wear gas mask with filter type A if cond b) Hand protection: Gloves. Materials nitrile rubber - materials (good resistance) Nitrile rubber. c) Eye protection: Protective goggles. d) Skin protection: Protective clothing. 8.2.3 Environmental exposure controls: See headings 6.2, 6.3 and 13	ed below. I description. If applicable and available, exposure scenarios are attached in annex. Always use the ed use. and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks h as personal protective equipment o not eat, drink or smoke during work. c. in air > exposure limit. Breakthrough time Thickness >480 minutes 0.35 mm	
 8.1.5 Control banding If applicable and available it will be listed. If applicable and available it will be listed. If applicable and available it will be listed. Exposure controls The information in this section is a general scenarios that correspond to your identified. 8.1.2 Appropriate engineering controls Use spark-/explosionproof appliances a concentration in the air regularly. 8.2.2 Individual protection measures, such Observe normal hygiene standards. Do a) Respiratory protection: Wear gas mask with filter type A if cond b) Hand protection: Gloves. Materials nitrile rubber - materials (good resistance) Nitrile rubber. c) Eye protection: Protective goggles. d) Skin protection: Protective clothing. 8.2.3 Environmental exposure controls: See headings 6.2, 6.3 and 13	ed below. I description. If applicable and available, exposure scenarios are attached in annex. Always use the ed use. and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks h as personal protective equipment o not eat, drink or smoke during work. c. in air > exposure limit. Breakthrough time Thickness >480 minutes 0.35 mm	
 8.1.5 Control banding If applicable and available it will be listed. Exposure controls The information in this section is a general scenarios that correspond to your identified scenarios and the air regularly. 8.2.2 Individual protection measures, such Observe normal hygiene standards. Do a) Respiratory protection: Wear gas mask with filter type A if conditions b) Hand protection: Gloves. Materials nitrile rubber • materials (good resistance) Nitrile rubber. • Dystection: Protective goggles. • Dystection: Protective goggles. • Stan protection: Protective clothing. 8.2.3 Environmental exposure controls: See headings 6.2, 6.3 and 13 • ON 9: Physical and chem • Information on basic physical ar	ed below. I description. If applicable and available, exposure scenarios are attached in annex. Always use the ed use. and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks h as personal protective equipment on to eat, drink or smoke during work. c. in air > exposure limit. Breakthrough time Thickness >480 minutes 0.35 mm	
 8.1.5 Control banding If applicable and available it will be listed. If applicable and available it will be listed. If applicable and available it will be listed. Exposure controls The information in this section is a general scenarios that correspond to your identified. 8.1.2 Appropriate engineering controls Use spark-/explosionproof appliances a concentration in the air regularly. 8.2.2 Individual protection measures, such Observe normal hygiene standards. Do a) Respiratory protection: Wear gas mask with filter type A if cond b) Hand protection: Gloves. Materials nitrile rubber - materials (good resistance) Nitrile rubber. c) Eye protection: Protective goggles. d) Skin protection: Protective clothing. 8.2.3 Environmental exposure controls: See headings 6.2, 6.3 and 13	ed below. I description. If applicable and available, exposure scenarios are attached in annex. Always use the ed use. and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks h as personal protective equipment o not eat, drink or smoke during work. c. in air > exposure limit. Breakthrough time Thickness >480 minutes 0.35 mm	
 8.1.5 Control banding If applicable and available it will be listed. Exposure controls The information in this section is a general scenarios that correspond to your identified scenarios and the air regularly. 8.2.2 Individual protection measures, such Observe normal hygiene standards. Do a) Respiratory protection: Wear gas mask with filter type A if conditions b) Hand protection: Gloves. Materials nitrile rubber • materials (good resistance) Nitrile rubber. • Dystection: Protective goggles. • Dystection: Protective goggles. • Stan protection: Protective goggles. • Stan protection: Protective clothing. 8.2.3 Environmental exposure controls: See headings 6.2, 6.3 and 13 • ON 9: Physical and chem • Information on basic physical ar Physical form	ed below. I description. If applicable and available, exposure scenarios are attached in annex. Always use the ed use. and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks h as personal protective equipment o not eat, drink or smoke during work. c. in air > exposure limit. breakthrough time Thickness >480 minutes 0.35 mm	
 8.1.5 Control banding If applicable and available it will be listed. Exposure controls The information in this section is a general scenarios that correspond to your identifie 8.2.1 Appropriate engineering controls Use spark-/explosionproof appliances a concentration in the air regularly. 8.2.2 Individual protection measures, such Observe normal hygiene standards. Do a) Respiratory protection: Wear gas mask with filter type A if cond b) Hand protection: Gloves. Materials nitrile rubber - materials (good resistance) Nitrile rubber. c) Eye protection: Protective goggles. d) Skin protection: Protective clothing. 8.2.3 Environmental exposure controls: See headings 6.2, 6.3 and 13 ON 9: Physical and chem Odour	ed below. I description. If applicable and available, exposure scenarios are attached in annex. Always use the ed use. and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks h as personal protective equipment o not eat, drink or smoke during work. c. in air > exposure limit. breakthrough time Thickness >480 minutes 0.35 mm	
 8.1.5 Control banding If applicable and available it will be liste If applicable and available it will be liste If applicable and available it will be liste Exposure controls The information in this section is a general scenarios that correspond to your identifie 8.2.1 Appropriate engineering controls Use spark-/explosionproof appliances a concentration in the air regularly. 8.2.2 Individual protection measures, such Observe normal hygiene standards. Do a) Respiratory protection: Wear gas mask with filter type A if cond b) Hand protection: Gloves. Materials nitrile rubber - materials (good resistance) Nitrile rubber. c) Eve protection: Protective goggles. d) Skin protection: Protective clothing. 8.2.3 Environmental exposure controls: See headings 6.2, 6.3 and 13 ION 9: Physical and chem Odour Odour threshold	ed below. I description. If applicable and available, exposure scenarios are attached in annex. Always use the ed use. and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks h as personal protective equipment onot eat, drink or smoke during work. c. in air > exposure limit. Breakthrough time Thickness >480 minutes 0.35 mm	

Reason for revision: 3.2; 13; 15.1

Publication date: 2008-03-20 Date of revision: 2016-06-14

Revision number: 0602

Flammability	Extremely flammable aerosol.	
Log Kow	Not applicable (mixture)	
Dynamic viscosity	1 mPa.s ; 20 °C ; Liquid	
Kinematic viscosity	1 mm²/s ; 20 °C ; Liquid	
Melting point	No data available	
Boiling point	No data available	
Flash point	61 °C ; Liquid	
Evaporation rate	0.04 ; butyl acetate ; Liquid	
Relative vapour density	>1	
Vapour pressure	8530 hPa ; 20 °C	
Solubility	water ; insoluble	
Relative density	0.81 ; 20 °C ; Liquid	
Decomposition temperature	No data available	
Auto-ignition temperature	255 °C ; Liquid	
Explosive properties	No chemical group associated with explosive properties	
Oxidising properties	No chemical group associated with oxidising properties	
рН	No data available	

9.2. Other information Absolute density

810 kg/m³ ; 20 °C ; Liquid

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

GT7 AEROSOL

No (test)data on the mixture available

white mineral oil (petroleum)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male/female)	Experimental value	
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5 mg/l	4 h	Rat (male/female)	Experimental value	
Irocarbons, C10-C13, I	n-alkanes, isc	alkanes, cyclics, < 2%	aromatics			-	
Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Route of exposure Oral	Parameter LD50	Method Equivalent to OECD 401	Value > 5000 mg/kg bw	Exposure time	Species Rat (male/female)		Remark
•		Equivalent to OECD		Exposure time		determination	Remark

Judgement is based on the relevant ingredients

Conclusion

Not classified for acute toxicity

Reason for revision: 3.2; 13; 15.1

Publication date: 2008-03-20 Date of revision: 2016-06-14

Revision number: 0602

Corrosion/irritation

GT7 AEROSOL

No (test)data on the mixture available

white mineral oil (petroleum)

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	Equivalent to OECD 404	24 h	24; 72 hours	Rabbit	Experimental value	
drocarbons, C10-C1	3, n-alkanes, isoal	anes, cyclics, < 2% arc	omatics		-	-	
Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment
Skin	Not irritating	Equivalent to OECD	4 h	24; 48; 72 hours	Rabbit	Read-across	

Judgement is based on the relevant ingredients

Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

Respiratory or skin sensitisation

GT7 AEROSOL

No (test)data on the mixture available

<u>wh</u>	white mineral oil (petroleum)									
R	oute of exposure	Result	Method			Species	Value determination	Remark		
_					point					
S	kin	Not sensitizing	Equivalent to OECD	24 h	48 hours	Guinea pig (male)	Experimental value			
			406							
hyd	drocarbons, C10-C1	3, n-alkanes, isoal	kanes, cyclics, < 2% ar	omatics						
R	oute of exposure	Result	Method	Exposure time	Observation time	Species	Value determination	Remark		
					point					
s	kin	Not sensitizing	Equivalent to OECD		24; 48 hours	Guinea pig	Read-across			
		_	406			(female)				

Judgement is based on the relevant ingredients

Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

GT7 AEROSOL

No (test)data on the mixture available

white mineral oil (petroleum)

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determinatior
Oral (diet)	NOAEL	OECD 453	≥ 1200 mg/kg bw/day		No effect	24 month(s)	Rat (male/female)	Experimental value
Oral (diet)	NOAEL	Equivalent to OECD 408	≥ 1600 mg/kg bw/day		No effect	90 day(s)	Rat (female)	Experimental value
Oral (diet)	LOEL	Equivalent to OECD 408	160 mg/kg bw/day		Histopathology	90 day(s)	Rat (female)	Experimental value
Dermal	NOAEL	Equivalent to OECD 410	1000 mg/kg bw/day		No adverse systemic effects	4 weeks (6h/day, 3 days/week)	Rabbit (male/female)	Read-across
Inhalation (aerosol)	NOEL	Equivalent to OECD 412	50 mg/m³	Lungs	No effect	4 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value
Inhalation (aerosol)	LOEL	Equivalent to OECD 412	210 mg/m³	Lungs	Weight changes	4 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value
rocarbons, C10-C13	, n-alkanes, is	oalkanes, cyclics	, < 2% aromatics		-		-	•
Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 422	≥ 1000 mg/kg bw/day		No effect		Rat (male/female)	Read-across
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	≥ 2200 mg/m³ air		No effect	14 weeks (6h/day, 5 days/week)	Rat (female)	Read-across

Reason for revision: 3.2; 13; 15.1

Publication date: 2008-03-20 Date of revision: 2016-06-14

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

GT7 AEROSOL

No (test)data on the mixture available

white mineral oil (petroleum)

ince minerar on (petroleanit)				
Result	Method	Test substrate	Effect	Value determination
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
Negative	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value
Negative	OECD 473	Chinese hamster ovary (CHO)	No effect	Read-across
drocarbons, C10-C13, n-alkane	s, isoalkanes, cyclics, < 2% arom	atics		
Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)	No effect	Read-across

Mutagenicity (in vivo)

GT7 AEROSOL

No (test)data on the mixture available

<u>whi</u>	hite mineral oil (petroleum)									
	Result	Method	Exposure time	Test substrate	Organ	Value determination				
	Negative	OECD 474		Mouse (male/female)	Bone marrow	Read-across				
hyd	ydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics									
[Result	Method	Exposure time	Test substrate	Organ	Value determination				
	-0	Equivalent to OECD 478		Rat (male)		Read-across				

Judgement is based on the relevant ingredients

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

GT7 AEROSOL

No (test)data on the mixture available

white mineral oil (petroleum)

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
exposure								determination
Dermal	NOEL	OECD 453	≥ 75 µl	104 weeks (3 times/week)	Mouse (male)	No carcinogenic effect		Experimental value
Oral	NOAEL	OECD 453	≥ 1200 mg/kg bw/day	24 month(s)	Rat (male/female)	No carcinogenic effect		Experimental value

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
exposure								determination
Inhalation	NOAEC	Equivalent to	≥ 2200 mg/m³ air	105 weeks (6h/day,	Rat (female)	No carcinogenic		Read-across
(vapours)		OECD 453		5 days/week)		effect		

Judgement is based on the relevant ingredients

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

GT7 AEROSOL

No (test)data on the mixture available

white mineral oil (petroleum)

	Parameter	Method	Value	Exposure time	Species	Effect	1.0.	Value determination
Developmental toxicity		Equivalent to OECD 414	> 5000 mg/kg bw/day	14 day(s)	Rat	No effect		Experimental value
Maternal toxicity		Equivalent to OECD 414	> 5000 mg/kg bw/day	14 day(s)	Rat	No effect		Experimental value
Effects on fertility	NOAEL (P/F1)		≥ 1000 mg/kg bw/day	7 weeks (daily) - 8 weeks (daily)	Rat (male/female)	No effect		Experimental value

Reason for revision: 3.2; 13; 15.1

Publication date: 2008-03-20 Date of revision: 2016-06-14

Revision number: 0602

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	- 0	Value determination
Developmental toxicity	NOAEC	Other	0,	10 days (6h/day)	Rat (female)	No effect		Read-across
Maternal toxicity	-		≥ 5220 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

GT7 AEROSOL

No (test)data on the mixture available

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Parameter	Method	Value	Organ	Effect	Exposure time	 Value determination
			Skin	Skin dryness or		Literature study
				cracking		

Chronic effects from short and long-term exposure

GT7 AEROSOL

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

GT7 AEROSOL

No (test)data on the mixture available white mineral oil (petroleum)

	Parameter	Method	Value	Duration	Species		Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 100 mg/l	96 h	Oncorhynchus mykiss	Static system		Experimental value; Nominal concentration
Acute toxicity invertebrates	LC50	OECD 202	> 100 mg/l	48 h	Daphnia magna	Static system		Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	NOEL	OECD 201	≥ 100 mg/l	72 h	Pseudokirchnerie Ila subcapitata	Static system		Weight of evidence; Growth rate
Long-term toxicity fish	NOEL		≥ 1000 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR
Long-term toxicity invertebrates	NOEL		≥ 1000 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR; Reproduction

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Duration	Species		Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 1000 mg/l	96 h		Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity invertebrates	EL50	OECD 202	> 1000 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	NOELR	OECD 201	> 1000 mg/l	72 h	Pseudokirchnerie Ila subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOELR	Other	0.101 mg/l	28 day(s)	Oncorhynchus mykiss			QSAR
Long-term toxicity invertebrates	NOELR	Other	0.176 mg/l	21 day(s)	Daphnia magna			QSAR
Toxicity aquatic micro- organisms	EL50	Other	> 1000 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR

Judgement is based on the relevant ingredients

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

white mineral oil (petroleum)

Method	Value	Duration	Value determination						
OECD 301F: Manometric Respirometry Test	31 %; GLP	28 day(s)	Read-across						
Phototransformation air (DT50 air)		÷							
Method	Value	Conc. OH-radicals	Value determination						
AOPWIN v1.90	0.1 day(s) - 0.6 day(s)	1500000 /cm ³	Calculated value						
nydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics									
Biodegradation water									
Method	Value	Duration	Value determination						
OECD 301F: Manometric Respirometry Test	80 %; GLP	28 day(s)	Read-across						
Biodegradation soil		· · ·							
Method	Value	Duration	Value determination						
memou		61 day(s)	Read-across						

Conclusion

Contains non readily biodegradable component(s)

The surfactant(s) is/are biodegradable

12.3. Bioaccumulative potential

GT7 AEROSOL

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

white mineral oil (petroleum)

Lo	Log Kow									
	Method	Remark	Value	Temperature	Value determination					
			> 6		Calculated					

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

white mineral oil (petroleum)

Percent distribution

м	ethod	Fraction air		Fraction sediment	Fraction soil	Fraction water	Value determination
M	ackay level III		0.1 %	55.85 %	43.57 %	0.09 %	Calculated value

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	65.8 %	0 %	22.9 %	9.6 %	1.7 %	Calculated value

Conclusion

Contains component(s) that adsorb(s) into the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

GT7 AEROSOL

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

white mineral oil (petroleum)

Ground water

Ground water pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

Reason for revision: 3.2; 13; 15.1

Publication date: 2008-03-20 Date of revision: 2016-06-14

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

13 02 05* (waste engine, gear and lubricating oils: mineral-based non-chlorinated engine, gear and lubricating oils). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14. <u>1</u> . UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Hazard identification number	23
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1. UN number		
UN number	1950	
14.2. UN proper shipping name		
Proper shipping name	Aerosols	
14.3. Transport hazard class(es)		
Class	2	
Classification code	5F	

14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	63
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Annex II of MARPOL 73/78	Not applicable

14.1. ON Humber	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
83.800 %	
542.379 g/l	

Ingredients according to Regulation (EC) No 648/2004 and amendments

≥30% aliphatic hydrocarbons, <5% anionic surfactants, perfumes, limonene, cinnamal

Reason for revision: 3.2; 13; 15.1

Publication date: 2008-03-20 Date of revision: 2016-06-14

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

and use of certain danger	ous substances, mixtures and articles.	
	Designation of the substance, of the group of	Conditions of restriction
	substances or of the mixture	
• white mineral oil (petroleum) • hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8	 Shall not be used in: ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, tricks and jokes, games for one or more participants, or any article intended to be used as such, even with ornamental aspects,2. Articles not complying with paragraph 1 shall not be placed on the market. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:

National legislation Belgium

GT7 AEROSOL

No data available

National legislation The Netherlands

<u>G</u>	GT7 AEROSOL					
	Waste identification (the	LWCA (the Netherlands): KGA category 06				
	Netherlands)					
	Waterbezwaarlijkheid	В (2)				

National legislation France

GT7 AEROSOL

No data available

National legislation Germany

GT7 AEROSOL				
WGK 1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wasserge				
Stoffe (VwVwS) of 27 July 2005 (Anhang 4)				
white mineral oil (petroleum)				
TA-Luft	5.2.5;1			
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
TA-Luft	5.2.5			

National legislation United Kingdom

GT7 AEROSOL

No data available

Other relevant data

GT7 AEROSOL
No data available
white mineral oil (petroleum)

white mineral on (petroleum)		
TLV - Carcinogen	Mineral oil, pure, highly and severely refined; A4	

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

Reason for revision: 3.2; 13; 15.1

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- (*) = INTERNAL CLASSIFICATION BY BIG
- PBT-substances = persistent, bioaccumulative and toxic substances

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3.2; 13; 15.1

Publication date: 2008-03-20 Date of revision: 2016-06-14

Revision number: 0602