

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



## SUPER AKTIVATOR

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : SUPER AKTIVATOR  
Registration number REACH : Not applicable (mixture)  
Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Adhesive  
Sealing compound  
Adhesive: activator

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

TEC7\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@tec7.be  
\*TEC7 is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Skin Irrit.	category 2	H315: Causes skin irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements



Contains: naphtha (petroleum), solvent-refined light.

Signal word Danger

##### H-statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

##### P-statements

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)  
Technische Schoolstraat 43 A, B-2440 Geel  
<http://www.big.be>  
© BIG vzw  
Reason for revision: 3.2; 8; 12  
Revision number: 0700

Publication date: 2000-09-20  
Date of revision: 2020-12-03

Product number: 32188

1 / 14

878-16433-002-en

# SUPER AKTIVATOR

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves, protective clothing and eye protection/face protection.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.

## 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
naphtha (petroleum), solvent-refined light	64741-84-0 265-086-6	30%≤C≤50%	Flam. Liq. 1; H224 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(6)(10)	Constituent	
propane 01-2119486944-21	74-98-6 200-827-9	10%≤C≤30%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant	
butane	106-97-8 203-448-7	10%≤C≤30%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas;	(1)(2)(10)(21)	Propellant	
isobutane 01-2119485395-27	75-28-5 200-857-2	1%≤C≤10%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas;	(1)(2)(10)(21)	Propellant	
N,N-dimethyl-p-toluidine	99-97-8 202-805-4	C<1 %	Acute Tox. 3; H331 Acute Tox. 3; H311 Acute Tox. 3; H301 STOT RE 2; H373 Aquatic Chronic 3; H412	(1)(10)	Constituent	

(1) For H- and EUH-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

(21) 1,3-butadiene <0.1%

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

#### After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

Coughing. Dizziness. Drowsiness.

##### After skin contact:

Red skin. Tingling/irritation of the skin.

##### After eye contact:

Redness of the eye tissue.

Reason for revision: 3.2; 8; 12

Publication date: 2000-09-20

Date of revision: 2020-12-03

Revision number: 0700

Product number: 32188

2 / 14

# SUPER AKTIVATOR

**After ingestion:**  
Dry/sore throat.

**4.2.2 Delayed symptoms**  
No effects known.

**4.3. Indication of any immediate medical attention and special treatment needed**  
If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.  
Major fire: Quantities of water.

### 5.2. Special hazards arising from the substance or mixture

Upon combustion: formation of CO, CO2 and small quantities of nitrous vapours. Pressurised container: May burst if heated.

### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034).

#### Suitable protective clothing

See heading 8.2

### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See heading 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Store in a cool area. Keep container in a well-ventilated place. Fireproof storeroom. Keep out of direct sunlight.

#### 7.2.2 Keep away from:

Heat sources, ignition sources, oxidizing agents, (strong) acids.

#### 7.2.3 Suitable packaging material:

No data available

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

# SUPER AKTIVATOR

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

##### Belgium

Butane, tous isomères: iso-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm

##### France

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m <sup>3</sup>

##### Germany

Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
Isobutan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m <sup>3</sup>

##### UK

Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m <sup>3</sup>

##### USA (TLV-ACGIH)

Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm
-----------------	--	----------

##### b) National biological limit values

If limit values are applicable and available these will be listed below.

##### USA (BEI-ACGIH)

Methemoglobin inducers (Methemoglobin)	Blood: during or end of shift	1,5 % of hemoglobin	Background, Nonspecific, Semi-quantative
Methemoglobin inducers (Methemoglobin)	Blood: during or end of shift	5 % of hemoglobin	Background, Nonspecific - Intended changes

#### 8.1.2 Sampling methods

Product name	Test	Number
N,N-Dimethyl p-Toluidine (Amines, Aromatic)	NIOSH	2002
Oil Mist (Mineral)	NIOSH	5026

#### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

#### 8.1.4 Threshold values

##### DNEL/DMEL - Workers

naphtha (petroleum), solvent-refined light

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1286.4 mg/m <sup>3</sup>	
	Long-term local effects inhalation	837.5 mg/m <sup>3</sup>	
	Acute local effects inhalation	1066.67 mg/m <sup>3</sup>	

N,N-dimethyl-p-toluidine

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1.224 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	0.694 mg/kg bw/day	

##### DNEL/DMEL - General population

naphtha (petroleum), solvent-refined light

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1152 mg/m <sup>3</sup>	
	Long-term local effects inhalation	178.57 mg/m <sup>3</sup>	
	Acute local effects inhalation	640 mg/m <sup>3</sup>	

Reason for revision: 3.2; 8; 12

Publication date: 2000-09-20

Date of revision: 2020-12-03

Revision number: 0700

Product number: 32188

4 / 14

# SUPER AKTIVATOR

## N,N-dimethyl-p-toluidine

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	0.302 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	0.347 mg/kg bw/day	
	Long-term systemic effects oral	0.174 mg/kg bw/day	

## PNEC

### N,N-dimethyl-p-toluidine

Compartments	Value	Remark
Fresh water	0.014 mg/l	
Marine water	0.001 mg/l	
Fresh water (intermittent releases)	0.137 mg/l	
STP	1.36 mg/l	
Fresh water sediment	48.245 mg/kg sediment dw	
Marine water sediment	48.245 mg/kg sediment dw	
Soil	20.365 mg/kg soil dw	

### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

#### c) Eye protection:

Protective goggles (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

### 8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available in the literature
Colour	Colourless
Particle size	Not applicable (aerosol)
Explosion limits	No data available in the literature
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	Not applicable (aerosol)
Kinematic viscosity	Not applicable (aerosol)
Melting point	No data available in the literature
Boiling point	No data available in the literature
Relative vapour density	No data available in the literature
Vapour pressure	No data available in the literature
Solubility	Water ; insoluble
Relative density	Not applicable (aerosol)
Absolute density	Not applicable (aerosol)
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	-40 °C ; Propellant
pH	Not applicable (aerosol)

### 9.2. Other information

Evaporation rate	No data available in the literature
Explosive properties	Not classified
Oxidising properties	Not classified

# SUPER AKTIVATOR

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

#### Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

### 10.5. Incompatible materials

Oxidizing agents, (strong) acids.

### 10.6. Hazardous decomposition products

Upon combustion: formation of CO, CO<sub>2</sub> and small quantities of nitrous vapours.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

#### Acute toxicity

##### SUPER AKTIVATOR

No (test) data on the mixture available

Judgement is based on the relevant ingredients

naphtha (petroleum), solvent-refined light

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 5.61 mg/l	4 h	Rat (male / female)	Read-across	

##### N,N-dimethyl-p-toluidine

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	1650 mg/kg bw		Rat (male / female)	Experimental value	
Oral			category 3			Annex VI	
Dermal	LD50	OECD 402	> 2000 mg/kg bw		Rabbit (male / female)	Experimental value	
Dermal			category 3			Annex VI	
Inhalation (aerosol)	LC50		1.4 mg/l	4 h	Rat	Experimental value	
Inhalation			category 3			Annex VI	

Classification of this substance according to Annex VI is debatable as it does not correspond to the conclusion from the test

#### Conclusion

Not classified for acute toxicity

#### Corrosion/irritation

##### SUPER AKTIVATOR

No (test) data on the mixture available

Classification is based on the relevant ingredients

naphtha (petroleum), solvent-refined light

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hrs; 4 days	Rabbit	Read-across	

# SUPER AKTIVATOR

## N,N-dimethyl-p-toluidine

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405	1 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

### Conclusion

Causes skin irritation.  
Not classified as irritating to the respiratory system  
Not classified as irritating to the eyes

### Respiratory or skin sensitisation

#### SUPER AKTIVATOR

No (test)data on the mixture available  
Judgement is based on the relevant ingredients  
naphtha (petroleum), solvent-refined light

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male)	Read-across	

## N,N-dimethyl-p-toluidine

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing				Rabbit (male / female)	QSAR	

### Conclusion

Not classified as sensitizing for inhalation  
Not classified as sensitizing for skin

### Specific target organ toxicity

#### SUPER AKTIVATOR

No (test)data on the mixture available  
Classification is based on the relevant ingredients  
naphtha (petroleum), solvent-refined light

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	Dose level	Subacute toxicity test	500 mg/kg bw/day	Kidney	Affection of the renal tissue	4 weeks (5 days / week)	Rat (male)	Read-across
Dermal	NOAEL	Equivalent to OECD 453	0.5 ml/kg bw		No effect		Mouse (male / female)	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 453	1.4 mg/l		No effect	107 weeks (6h / day, 5 days / week) - 109 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across
Inhalation (vapours)			STOT SE cat.3		Drowsiness, dizziness			Literature study

## N,N-dimethyl-p-toluidine

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	LOAEL		6 mg/kg bw/day	Female reproductive organ	Impairment/d egeneration	105 weeks (5 days / week)	Rat (female)	Experimental value
Oral (stomach tube)	LOAEL		62.5 mg/kg	Various organs	Weight changes	14 weeks (5 days / week)	Rat (male / female)	Experimental value
Dermal			STOT RE cat.2					Annex VI
Dermal								Data waiving
Inhalation (vapours)	LOEL		67.28 mg/kg bw/day		Body weight reduction		Rat (male / female)	QSAR

### Conclusion

May cause drowsiness or dizziness.  
Not classified for subchronic toxicity

### Mutagenicity (in vitro)

#### SUPER AKTIVATOR

No (test)data on the mixture available  
Judgement is based on the relevant ingredients

Reason for revision: 3.2; 8; 12

Publication date: 2000-09-20

Date of revision: 2020-12-03

Revision number: 0700

Product number: 32188

7 / 14

# SUPER AKTIVATOR

naphtha (petroleum), solvent-refined light

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)		Read-across	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Read-across	

N,N-dimethyl-p-toluidine

Result	Method	Test substrate	Effect	Value determination	Remark
Negative	OECD 471	Bacteria (S.typhimurium)		Experimental value	

## Mutagenicity (in vivo)

### SUPER AKTIVATOR

No (test)data on the mixture available

Judgement is based on the relevant ingredients

naphtha (petroleum), solvent-refined light

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))	EPA OPPTS 870.5395	4 weeks (6h / day, 5 days / week)	Rat (male / female)		Read-across

### Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### SUPER AKTIVATOR

No (test)data on the mixture available

Judgement is based on the relevant ingredients

naphtha (petroleum), solvent-refined light

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	Dose level	Equivalent to OECD 451	9869 mg/m <sup>3</sup>	113 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Read-across

### Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

### SUPER AKTIVATOR

No (test)data on the mixture available

Judgement is based on the relevant ingredients

naphtha (petroleum), solvent-refined light

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	23900 mg/kg bw/day	15 days (gestation, daily)	Rat	No effect		Read-across
Maternal toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	23900 mg/m <sup>3</sup>	15 days (gestation, daily)	Rat	No effect		Read-across
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	≥ 20000 mg/m <sup>3</sup>		Rat (male / female)	No effect		Read-across

N,N-dimethyl-p-toluidine

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Effects on fertility	LOAEL (F2)		72.98 mg/kg bw/day		Rat (male / female)			QSAR

### Conclusion

Not classified for reprotoxic or developmental toxicity

## Toxicity other effects

### SUPER AKTIVATOR

No (test)data on the mixture available

## Chronic effects from short and long-term exposure

### SUPER AKTIVATOR

No effects known.

## 11.2. Information on other hazards

Reason for revision: 3.2; 8; 12

Publication date: 2000-09-20

Date of revision: 2020-12-03

Revision number: 0700

Product number: 32188

8 / 14



# SUPER AKTIVATOR

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

#### SUPER AKTIVATOR

No (test) data on the mixture available

Classification is based on the relevant ingredients

naphtha (petroleum), solvent-refined light

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	10 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	OECD 202	4.5 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	EL50	OECD 201	3.1 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity aquatic crustacea	NOELR	OECD 211	2.6 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value

N,N-dimethyl-p-toluidine

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		46 mg/l	96 h	Pimephales promelas		Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	ECOSAR	15.26 mg/l	48 h	Daphnia magna			QSAR
Toxicity algae and other aquatic plants	EC50		24.3 mg/l	72 h	Pseudokirchneriella subcapitata	Flow-through system	Fresh water	QSAR
Long-term toxicity fish	LC50	ECOSAR	24.89 mg/l	14 day(s)				QSAR
Long-term toxicity aquatic crustacea								Data waiving
Toxicity aquatic micro-organisms	EC50		42.86 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR

#### Conclusion

Toxic to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

naphtha (petroleum), solvent-refined light

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	77 %	28 day(s)	Experimental value

N,N-dimethyl-p-toluidine

#### Biodegradation water

Method	Value	Duration	Value determination
EPA OPPTS 835.3210	50 %	38 day(s)	Calculated value

#### Conclusion

##### Water

Contains non readily biodegradable component(s)

### 12.3. Bioaccumulative potential

#### SUPER AKTIVATOR

##### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

naphtha (petroleum), solvent-refined light

#### BCF other aquatic organisms

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBFAF v3.01	1216 l/kg; Fresh weight			Estimated value

#### Log Kow

Method	Remark	Value	Temperature	Value determination
KOWWIN		4.27		Estimated value

Reason for revision: 3.2; 8; 12

Publication date: 2000-09-20

Date of revision: 2020-12-03

Revision number: 0700

Product number: 32188

9 / 14

# SUPER AKTIVATOR

N,N-dimethyl-p-toluidine

## BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	EPA OTS 797.1520	33		Pisces	Calculated value

## Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		1.729	35 °C	Experimental value

## Conclusion

Contains bioaccumulative component(s)

## 12.4. Mobility in soil

naphtha (petroleum), solvent-refined light

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	2.640	Calculated value

### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Fugacity Model Level III	31.8 %		0.867 %	1.27 %	66.1 %	Calculated value

N,N-dimethyl-p-toluidine

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	2.1	Calculated value

## Conclusion

Contains component(s) with potential for mobility in the soil

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

### SUPER AKTIVATOR

#### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

N,N-dimethyl-p-toluidine

#### Groundwater

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Not classified as hazardous waste when part A and part B are mixed and are fully cured. Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09\* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other hazardous substances).

14 06 03\* (waste organic solvents, refrigerants and foam/aerosol propellants: other solvents and solvent mixtures). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Should not be landfilled with household waste. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

Reason for revision: 3.2; 8; 12

Publication date: 2000-09-20

Date of revision: 2020-12-03

Revision number: 0700

Product number: 32188

10 / 14

# SUPER AKTIVATOR

## SECTION 14: Transport information

### Road (ADR)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	Aerosols
14.3. Transport hazard class(es)	Hazard identification number	
	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	yes
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Rail (RID)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	Aerosols
14.3. Transport hazard class(es)	Hazard identification number	23
	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	yes
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Inland waterways (ADN)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	Aerosols
14.3. Transport hazard class(es)	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	yes
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Sea (IMDG/IMSBC)

14.1. UN number	UN number	1950
-----------------	-----------	------

# SUPER AKTIVATOR

14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	P
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable

## Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
51 % - 100 %	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· naphtha (petroleum), solvent-refined light · N,N-dimethyl-p-toluidine	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly,

Reason for revision: 3.2; 8; 12

Publication date: 2000-09-20

Date of revision: 2020-12-03

Revision number: 0700

Product number: 32188

12 / 14

# SUPER AKTIVATOR

		<p>legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";</p> <p>b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";</p> <p>c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.</p> <p>6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled H304, intended for supply to the general public.</p> <p>7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'</p>
naphtha (petroleum), solvent-refined light	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	<p>1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:</p> <ul style="list-style-type: none"> <li>— metallic glitter intended mainly for decoration,</li> <li>— artificial snow and frost,</li> <li>— "whoopee" cushions,</li> <li>— silly string aerosols,</li> <li>— imitation excrement,</li> <li>— horns for parties,</li> <li>— decorative flakes and foams,</li> <li>— artificial cobwebs,</li> <li>— stink bombs.</li> </ul> <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:</p> <p>"For professional users only".</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>

## National legislation Belgium

### SUPER AKTIVATOR

No data available

## National legislation The Netherlands

### SUPER AKTIVATOR

Waterbezwaarlijkheid	Z (2); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

## National legislation France

### SUPER AKTIVATOR

No data available

## National legislation Germany

### SUPER AKTIVATOR

WGK	3; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
-----	--

### naphtha (petroleum), solvent-refined light

TA-Luft	5.2.5/I
---------	---------

### N,N-dimethyl-p-toluidine

TA-Luft	5.2.5/I
---------	---------

## National legislation United Kingdom

### SUPER AKTIVATOR

No data available

## Other relevant data

### SUPER AKTIVATOR

No data available

### N,N-dimethyl-p-toluidine

IARC - classification	2B; Dimethyl-p-toluidine
-----------------------	--------------------------

## 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under heading 3:

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H224 Extremely flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H301 Toxic if swallowed.

Reason for revision: 3.2; 8; 12

Publication date: 2000-09-20

Date of revision: 2020-12-03

Revision number: 0700

Product number: 32188

13 / 14

# SUPER AKTIVATOR

H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H315 Causes skin irritation.  
H331 Toxic if inhaled.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs (reproductive organs) through prolonged or repeated exposure if swallowed.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.